

GASSOFLEX AAE



Aplicaciones

Gassoflex AAE es recomendada para la impulsión y/o aspiración de carburantes, aceites y lubricantes tanto en camiones cisternas, vagones o en planta, pero gracias a sus espirales en aluminio es significativamente mas ligera haciendo su manejo mas facil especialmente en grandes diametros

AAE

Serie Standard: 10100

Serie Pesada: 14100

Construcción:

- Espiral Interior: Aluminio (A)
- Espiral Exterior: Aluminio (A)
- Forro Interior: Polipropileno (E)
- Cubierta: Polipropileno

Gama de Temperatura: -20°C a +100°C

Factor de Seguridad:

La presión de trabajo esta basada en un fator de seguridad 5:1

Applications

Gassoflex AAE is recommended for the delivery and/or suction of fuels, oils and lubricants in cistern trucks, railcars or fixed deposits. However, due to its aluminium wire spiral it is significantly lighter and easier to handle especially in large diameters.

AAE

Standard Series: 10100

Heavy Series: 14100

Construction:

- Inner Wire spiral: Aluminium (A)
- Outer Wire spiral: Aluminium (A)
- Inner Lining: Polypropylene (E)
- Cover: Polypropylene

Temperature range: -20°C a +100°C

Work Safety factor:

The working pressure is based on a safety factor of 5:1

Código Gassó Gassó code	Presión trabajo Working press.		Diámetro Diameter	Radio curvatura Curve radius	Peso Weight	Longitud máx. rollos Max. coil lengths
	(bar)	(PSI)				

GASSOFLEX 10100 AAE

—	10	150	1	51	0,37	35
—	10	150	1 1/4	55	0,48	35
—	10	150	1 1/2	78	0,65	35
AIA7501	10	150	2	142	1,00	35
AIA7651	10	150	2 1/2	170	1,45	35
AIA1010	10	150	3	218	1,70	35
AIA101	10	150	4	240	2,97	35

GASSOFLEX 14100 AAE

—	14	210	1	51	0,37	35
—	14	210	1 1/4	55	0,48	35
—	14	210	1 1/2	78	0,65	35
—	14	210	2	142	1,00	35
—	14	210	2 1/2	170	1,45	35
—	14	210	3	218	1,70	35
—	14	210	4	240	2,97	35

CUSTOMIZE



Consultar otra configuración posible

Other configurations on request:
AGE, GAE, SGE, ...

