

GASSOFLEX MARINE HEAVY DUTY



Aplicaciones

Gassoflex MARINE HEAVY DUTY son utilizadas en la carga/descarga de barcos en aplicaciones marinas de gran robustez. Dependiendo del producto a transvasar podemos elegir entre las diferentes configuraciones de forro interior y espirales la mas adecuada para la aplicacion.

EGE/ GGE/SSE/SST

Serie Standard: 14100

Construcción:

- Espiral Interior: Acero galvanizado (G) o acero inoxidable 316 (S)
- Espiral Exterior: Acero galvanizado (G) o acero inoxidable 316 (S)
- Forro Interior: Polipropileno (E) o P.T.F.E. (T)
- Cubierta: Polipropileno

Gama de Temperatura: -20°C a +100°C

Factor de Seguridad:

La presión de trabajo esta basada en un fator de seguridad 5:1

Applications

Gassoflex MARINE HEAVY DUTY is used in the loading/unloading of boats in marine applications which require a more robust hose. The product to be transferred will pre-determine the most adequate configuration of the inner lining and inner and outer wire spirals. Various possibilities exist.

EGE/ GGE/SSE/SST

Standard Series: 14100

Construction:

- Inner Wire spiral: Galvanized Steel (G) or Stainless Steel 316 (S)
- Outer Wire spiral: Galvanized Steel (G) or Stainless Steel 316 (S)
- Inner Lining: Polypropylene (E) or P.T.F.E. (T)
- Cover: Polypropylene

Temperature range: -20°C a +100°C

Work Safety factor:

The working pressure is based on a safety factor of 5:1

Código Gassó Gassó code	Tipo Type	Presión trabajo Working press.		Diámetro Diameter	Radio curvatura Curve radius	Peso Weight	Longitud máx. rollos Max. coil lengths
		(bar)	(PSI)				

GASSOFLEX MARINE HEAVY DUTY 14100

AIA1051	EGE	14	210	6	497	12	20
AIA111	EGE	14	210	8	740	22	20
AIA115	EGE	14	210	10	920	30	20
AIA202	GGE	14	210	6	497	12	20
AIA112	GGE	14	210	8	740	22	20
AIA113	GGE	14	210	10	920	30	20
AIA4004	SSE	14	210	6	497	12	20
AIA4006	SSE	14	210	8	740	22	20
AIA106	SST	14	210	6	497	12	20
AIA1061	SST	14	210	8	740	22	20

CUSTOMIZE



Consultar otra configuración posible

Other configurations on request:
EEE, ESE, ...

