

GASSOFLEX SGE



Aplicaciones

Gassoflex SGE es recomendada para la impulsión y/o aspiración de una gran variedad de productos químicos compatibles con el polipropileno y el inoxidable y que no tengan contacto con la manguera exteriormente, en camiones cisternas, vagones o en planta.

SGE

Serie Standard: 10100

Serie Pesada: 14100

Construcción:

- Espiral Interior: Acero inoxidable 316 (S)
- Espiral Exterior: Acero galvanizado (G)
- Forro Interior: Polipropileno (E)
- Cubierta: Polipropileno

Gama de Temperatura: -20°C a +100°C

Factor de Seguridad:

La presión de trabajo está basada en un factor de seguridad 5:1

Applications

Gassoflex SGE is recommended for the delivery and/or suction of a wide range of chemical products compatible with any polypropylene or stainless steel which may not come in contact with the external part of the hose. It is used in cistern trucks, railcars and fixed deposits.

SGE

Serie Standard: 10100

Serie Pesada: 14100

Construction:

- Inner Wire spiral: Stainless Steel 316 (S)
- Outer Wire spiral: Galvanized Steel (G)
- Inner Lining: Polypropylene (E)
- Cover: Polypropylene

Temperature range: -20°C a +100°C

Work Safety factor:

The working pressure is based on a safety factor of 5:1

Código Gassó Gassó code	Presión trabajo Working press.		Diámetro Diameter	Radio curvatura Curve radius	Peso Weight	Longitud máx. rollos Max. coil lengths
	(bar)	(PSI)				

GASSOFLEX 10100 SGE

AIA2321	10	150	1	68	0,85	35
AIA232	10	150	1 1/4	74	1,07	35
AIA240	10	150	1 1/2	105	1,50	35
AIA250	10	150	2	190	2,00	35
AIA265	10	150	2 1/2	225	3,05	35
AIA275	10	150	3	290	3,55	35
AIA276	10	150	4	320	6,40	35

GASSOFLEX 14100 SGE

—	14	210	1	68	0,85	35
—	14	210	1 1/4	74	1,07	35
—	14	210	1 1/2	105	1,50	35
—	14	210	2	190	2,00	35
—	14	210	2 1/2	225	3,05	35
—	14	210	3	290	3,55	35
AIA4000	14	210	4	320	6,40	35

CUSTOMIZE



Consultar otra configuración posible
Other configurations on request:
EEE, ESE, ...

