

GASSOFLEX SSE



Aplicaciones

Gassoflex SSE es recomendada para la impulsión y/o aspiración de una gran variedad de productos químicos compatibles con el polipropileno y el inoxidable y que tengan contacto con la manguera tanto interior como exteriormente, en camiones cisternas, vagones o en planta.

SSE

Serie Standard: 10100

Serie Pesada: 14100

Construcción:

- Espiral Interior: Acero inoxidable 316 (S)
- Espiral Exterior: Acero inoxidable 316 (S)
- Forro Interior: Polipropileno (E)
- Cubierta: Polipropileno

Gama de Temperatura: -20°C a +100°C

Factor de Seguridad:

La presión de trabajo está basada en un factor de seguridad 5:1

Applications

Gassoflex SSE is recommended for the delivery and/or suction of a wide range of chemical products compatible with any polypropylene and stainless steel which may come in contact with the hose both internally or externally in tank trucks, railcars or fixed deposits.

SSE

Standard Series: 10100

Heavy Series: 14100

Construction:

- Inner Wire spiral: Stainless Steel 316 (S)
- Outer Wire spiral: Stainless Steel 316 (S)
- Inner Lining: Polypropylene (E)
- Cover: Polypropylene

Temperature range: -20°C a +100°C

Work Safety factor:

The working pressure is based on a safety factor of 5:1

Código Gassó Gassó code	Presión trabajo Working press.		Diámetro Diameter	Radio curvatura Curve radius	Peso Weight	Longitud máx. rollos Max. coil lengths
	(bar)	(PSI)				

GASSOFLEX 10100 SSE

AIA325	10	150	1	68	0,85	35
AIA332	10	150	1 1/4	74	1,07	35
AIA340	10	150	1 1/2	105	1,50	35
AIA350	10	150	2	190	2,00	35
AIA351	10	150	2 1/2	225	3,05	35
AIA375	10	150	3	290	3,55	35
AIA400	10	150	4	320	6,40	35

GASSOFLEX 14100 SSE

—	14	210	1	68	0,85	35
—	14	210	1 1/4	74	1,07	35
—	14	210	1 1/2	105	1,50	35
—	14	210	2	190	2,00	35
—	14	210	2 1/2	225	3,05	35
—	14	210	3	290	3,55	35
AIA4000	14	210	4	320	6,40	35

CUSTOMIZE



Consultar otra configuración posible

Other configurations on request:

EEE, ESE, ...

